

PRESSURE *is* Our BUSINESS



Introducing the next

BIG THING

Precision & Performance
at an **affordable price!**



P R E S S U R E

Actual size!

DO MORE WITH LESS

0.2% of reading accuracy!

One M1 replaces several ordinary pressure gauges

Fully compensated!

No change in accuracy from -10°C (14°F) to 50°C (122°F)

Easy to read 5 digit display!

Large 17mm (0.66") numbers with a bright backlight

Up to 30,000 hours of service!

Runs on just two AA alkaline batteries

Housing and boot are compatible with many industrial fluids including Skydrol®



Crystal Engineering designed and manufactures the M1. Our gauges are tested and calibrated inside environmental test chambers using computer controlled pressure controllers. Every M1 comes with a certificate with calibration data at -10°C, 15°C, 25°C, 35°C and 50°C. We have devoted over 20 years to the engineering and manufacturing of pressure calibrators, pressure gauges and pressure measuring equipment for industries worldwide.

www.crystalengineering.net

CRYSTAL
engineering corporation



SPECIFICATIONS

ACCURACY

20% to 100% of Full Scale:
±(0.2% of Reading).

0 to 20% of Full Scale:
±(0.04% of Full Scale).

Vacuum, for 2MPa (300 PSI, 20 bar, 20kg/cm²) and lower pressure gauges:

0 to -99.9 kPa (-14.5 PSIG):
±(0.25% of Full Scale),
where F.S.: -99.9 kPa (-14.5 PSIG).
Not recommended for continuous use at high vacuum.

TEMPERATURE

Operating & Compensated:
-10°C to 50°C (14°F to 122°F).

No change in accuracy over operating temperature range.
Gauge must be zeroed to achieve rated specification.

Storage: -40°C to 75°C (-40°F to 167°F).

ENCLOSURE

Description: Water resistant housing incorporating o-ring seals. Polyester/ Polycarbonate blend compatible with common industrial fluids, including Skydrol. IP65.

Weight: 325g (11.5 oz).
including batteries and protective boot.

CONNECTIONS

Pressure Connection: 1/4" NPT or G 1/4 B (BSP parallel fitting).

DISPLAY

Numeral Height: 16.8mm (0.66").

Description: 5 full digits.

Display Rate: 4 readings/second.

SENSOR

Piezoresistive silicon sensor with permanent oil isolation system and integral filter.

316 stainless steel welded (not brazed) sensor. No o-rings, thread tape, epoxy or sealant on any part of sensor assembly.

POWER

Battery: Two AA alkaline (LR6) batteries.

Standard Battery Life: 900 hours at 4 readings/second.

Extended Battery Life:

- 1 reading/15 seconds ... **3,000 hours**
- 1 reading/30 seconds ... **6,000 hours**
- 1 reading/1 minute ... **10,000 hours**
- 1 reading/5 minutes ... **25,000 hours**
- 1 reading/10 minutes ... **30,000 hours**

1/4" NPT

G 1/4 B

MEDIA COMPATIBILITY

Liquids and gases compatible with 316 stainless steel.

Available cleaned for oxygen service.

OVER SCALE LIMIT

Display will flash at 110% of Full Scale.


ADDITIONAL FEATURES

Vertical bar graph

Minimum (LO) & maximum (HI) capture

Averaging

(2 to 20 samples).

 Specifications include linearity, hysteresis, repeatability, temperature and stability for one year.

ORDERING INFORMATION


Pressure Units and Resolution														
PSI ¹	Pa ²	bar ¹	kg/cm ² ¹	Over-pressure	PSI	kPa	MPa	bar	mbar	kg/cm ²	inch H ₂ O ³	inch Hg	mm H ₂ O	mm Hg
30PSI	200KPA	2BAR	2KG	3.0 x	0.001	0.01		0.0001	0.1	0.0001	0.1	0.01	1	0.1
100PSI	1MPA	10BAR	10KG	2.0 x	0.01	0.1	0.0001	0.001	1	0.001	0.1	0.01		1
300PSI	2MPA	20BAR	20KG	2.0 x	0.01	0.1	0.0001	0.001	1	0.001		0.1		1
1KPSI	10MPA	100BAR	100KG	2.0 x	0.1	1	0.001	0.01		0.01		0.1		
3KPSI	20MPA	200BAR	200KG	1.5 x	0.1	1	0.001	0.01		0.01		1		
10KPSI	70MPA	700BAR	700KG	1.5 x	1		0.01	0.1		0.1		1		

¹ PSI, BAR and KG models can display all available pressure units. ² KPA/MPA versions can display pressure in kPa, MPa, bar, and mbar only.

³ Density of water can be set to 4°C, 60°F or 20°C /68°F with the keypad. ⁴ Applies to 100PSI gauge. 1MPa, 10BAR and 10KG units will be 0.1 PSI.

⁵ Disabled for 1MPa, 10BAR and 10KG units.

M1 PART NUMBERING SYSTEM



SAMPLE PART NUMBERS

M1-300PSI

A 300 PSI gauge with the 1/4" (male) NPT connection fitting

M1-200KPA-BSP

A 200 kPa gauge with the G 1/4 B (BSPP) connection fitting

M1-20BAR-BSP-O

A 20 bar gauge with the G 1/4 B (BSPP) connection fitting and cleaned for oxygen service



CRYSTAL
engineering corporation