



905U-E Wireless Ethernet Modem

Long-range wireless Ethernet for reliable industrial connectivity



Description

The ELPRO 905U-E Wireless Ethernet Modem is a robust, license-free wireless transceiver capable of long-range communications to 20 miles (32 km). Operating at 900 MHz and up to 1W, the 802.11 standards-based ELPRO 905U-E provides reliable and secure two-way wireless communications in complex applications connecting PLCs, DCS and SCADA systems, data loggers, or field instruments in challenging outdoor environments typical of industrial monitoring and control applications.

Capable of operating in access point client configuration, functioning as a network bridge/router, or serving as a serial server (RS-232/RS-485), the ELPRO 905U-E offers node-to-node, node-to-multi-node, and repeater functionality for scalability, with additional I/O expansion delivered through the use of ELPRO 115S expansion modules. Security measures using MAC address/IP filtering and encryption to 128-bit AES provide increased reliability.

Features

- 902–928 MHz frequency and up to 1W RF power (subbands configurable)
- FHSS to 200 kbps data throughput
- Bridge/router, access point client-configurable
- Serial client/server/multicast Modbus® TCP to RTU gateway/Modbus
- Point-to-point or multipoint functionality, with simultaneous use of RJ-45, RS-232/RS-485 ports
- 10/100Base-T IEEE 802.3 Ethernet, RJ-45 connector
- Spanning tree (self-healing) support
- Security to 128-bit AES encryption
- MAC address/IP filtering
- Over-the-air network diagnostics and configuration
- On-board discrete I/O channel for failure status

Applications

- PLC communications
- Data logger communications
- Serial and Ethernet communications
- SCADA networks
- Water/wastewater systems
- Gas wellhead RTU communications

Specifications

SPECIFICATION	DESCRIPTION
Transmitter and Receiver	
Frequency	902–928 MHz ① 915–928 MHz ②
Transmit power	0.1–1W (configurable)
Transmission	Frequency hopping spread spectrum (FHSS)
Modulation	Frequency shift keying
Receiver sensitivity	–106 dBm @ 19.2 kbps, –103 dBm @ 115.2 kbps (1% FER)
Channel spacing	50 x 250 kHz
Data rate	19.2–200 kbps Auto mode selects fastest rate possible relative to RSSI
Range (LoS)	20 miles (32 km) @ 4W EIRP ③
Antenna connector	Female SMA standard polarity
Input and Output	
Discrete I/O	Input voltage-free contact ④ Output FET 30 Vdc 500 mA ④
Ethernet Port	
Ethernet port	10/100Base-T, RJ-45 connector, IEEE 802.3
Serial Port	
RS-232	DB-9 female DCE, RTS/CTS/DTR/DCD
RS-485	2-pin terminal block ⑤
Data rate (bps)	1200, 2400, 4800, 9600, 14400, 19200, 38400, 57600, 76800, 115200, 230400
Serial settings	7/8 data bits, stop/start/parity (configurable)
Protocols and Configuration	
System address	ESSID, 1 to 31-character text string
Protocols supported	TCP/IP, UDP, ARP, PPP, ICMP, HTTP, FTP, TFTP, TELNET, Modbus TCP
User configuration	User-configurable parameters via HTTPS embedded Web server
Configurable parameters	Access point/client/bridge/router Broadcast/control point to point, point to multipoint Modbus TCP/RTU gateway Serial client/server/multicast Simultaneous RS-232/RS-485 connection
Security	128-bit AES, 64-bit proprietary encryption 256 characters (alphanumeric)
Bandwidth protection	MAC address, whitelist/blacklist IP filtering, whitelist/blacklist ARP/GARP filtering, whitelist/blacklist
LED Indication and Diagnostics	
LED indication	Power/OK, RX, TX, link, LAN, serial, digital I/O status
Reported diagnostics	RSSI measurements (dBm) Connectivity information/statistics System log file
Power Supply	
Nominal supply	10–30 Vdc, under/over voltage protection
Average current draw	220 mA @ 12V (idle), 120 mA @ 24V (idle)
Transmit current draw	550 mA @ 12V (1W), 290 mA @ 24V (1W)
General	
Size	4.5" x 5.5" x 1.2" (114 mm x 140 mm x 30 mm)
Housing	Powder-coated aluminum
Mounting	DIN rail
Terminal blocks	Removable, max. conductor 12 AWG 0.1 in. ² (2.5 mm ²)
Temperature rating	–40 to +140°F (–40 to +60°C)
Humidity rating	0–99% RH noncondensing
Weight	0.8 lb (0.45 kg)

SPECIFICATION	DESCRIPTION
Compliance	
EMC	FCC Part 15
RF (radio)	FCC Part 15.247; RSS 210
Hazardous area	CSA Class I, Division 2; AS/NZS 4268
Safety	IEC 60950 (RoHS compliant)

Note: Specifications are subject to change.

- ① Configured for US
- ② Configured for Australia, Brazil
- ③ Typical maximum line-of-sight range (country dependent)
- ④ Can be used to transfer I/O status or communications failure output
- ⑤ Maximum distance 4000' (1.2 km)

Ordering

PRODUCT CODE	DESCRIPTION	FREQUENCY	RF POWER
905U-E-900-1W	905U-E wireless Ethernet	902–928 MHz	1W

Note: Available RF power and frequency may vary depending on country of application.

Accessories

PRODUCT CODE	DESCRIPTION
Antennas - 900 MHz	
DG900-1/5	Whip antenna, SMA male, angle bracket, –2 dBi gain, 3' (1m) coaxial cable
WH900-SMA	Whip antenna, SMA male, –2 dBi gain
CFD890EL	Dipole antenna, SMA male, mounting bracket, 2 dBi gain, 16' (5m) coaxial cable
SG900EL	Collinear antenna, N-type female, 5 dBi gain
SG900-6	Collinear antenna, N-type female, 8 dBi gain
YU6-900	Yagi antenna, N-type female, 9 dBi gain
YU16-900	Yagi antenna, N-type female, 15 dBi gain
Cables	
CC3/10/20-SMA	Coaxial cable kit, 9.8' (3m)/32' (10m)/65' (20m), N-type to SMA
CCTAIL-SMA-F/M	Coaxial cable tail, 24" (0.6m), SMA to N-type female or male
ETH-C5X	Ethernet cable, 6' (1.8m), crossover, RJ-45 to RJ-45
ETH-C5A	Ethernet cable, 6' (1.8m), straight through, RJ-45 to RJ-45
SER-DB9	Serial RS-232 cable, DB-9 male to DB-9 female, straight through
SER-RJ45	RS-232 serial cable, DB-9 female to RJ-45
Surge Diverters	
CSD-SMA-2500	SMA surge diverter for use with CC10/CC20–SMA
CSD-N-6000	Coaxial surge diverter, bulkhead N female to N female
MA15/D/1/SI	Power supply surge diverter, 110 Vdc/15A
IOP32D	Signal surge diverter, 2 x 2-wire/1 x 4-wire
Power Supplies	
PS-DINAC-12DC-OK	DIN rail power supply, 100–250 Vac, 12 Vdc/2.5A
PSG60E	DIN rail power supply, 85–264 Vac, 24 Vdc/2.5A
Mounting Brackets	
BR-COL-KIT	Mounting bracket kit for collinear antenna
BR-YAG-KIT	Mounting bracket kit for Yagi antenna



ELPRO Technologies

9/12 Billabong Street
Stafford Queensland 4053 Australia

Telephone:
Global: +61 7 3352 8600
USA: +1 855 443 5776

sales@elpro.com.au
www.elpro.com.au

© 2018 ELPRO Technologies
All Rights Reserved
Publication No. EL-905U-E
September 2018

ELPRO Technologies is a registered
trademark.

All other trademarks are property
of their respective owners.